

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/16/16	


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





PACKAGED IN TUBES

Positions: 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60
A = .079 [2.00] x No. of Spaces
B = .079 [2.00] x No. of Spaces + .134 [3.40]
C = .079 [2.00] x No. of Spaces + .161 [4.10]

SPECIFICATIONS:
Material:
Insulator: Hi-Temp Thermoplastic, 30% GF, rated UL 94V-0
Insulator color: Black
Contacts: Brass
Plating:
Gold flash over Nickel underplate on contact area,
Tin over Copper underplate on PCB tails
Electrical:
Current rating: 2.0 Amp
Contact resistance: 20 mohms max
Insulation resistance: 1,000 Mohms min
Dielectric withstanding voltage: 500 VAC/DC for 1 minute
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	3/16/16
CHECKED	CT	3/16/16
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: 2.00MM DUAL ROW, VERTICAL MOUNT BOX HEADER, SEL-GOLD PLATED

SIZE	PART NO.	REV.
X	2BHR-XX-VSGA-PE	-

REF: S00019C | SCALE: NTS | SHEET 1 OF 1