


Rev	AWO #	Description	Date	Appr
-		RELEASED	3/5/18	

APPROVED: _____


DATE: _____ TITLE: _____








SECTION A–A



SECTION B–B



SECTION C–C

SPECIFICATIONS:
Material:
Contact: Phosphor Bronze
Thickness: .008 [0.20mm]
Plating:
Tin over Copper underplate overall
Electrical:
Current rating: 3 A AC/DC
Contact resistance: 20 mohms max
Insulation resistance: 1,000 Mohms min
Dielectric withstanding voltage: 1,000 VAC for 1 minute
Mechanical:
Wire range: 22–30 AWG
Temperature Rating:
–25°C to +85°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	3/5/18
CHECKED	IC	3/5/18
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE
.079 [2.00] PITCH CRIMP CONTACT, FOR 2CH-K1

SIZE	PART NO.	REV.
X	2CTK1-R	-

REF:	SCALE:	SHEET
S00124T	NTS	1 OF 1