

APPROVED: _____


DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-	8909	RELEASED	7/30/08	
A		REVISED SHAPE	3/16/15	AY/TW







RECOMMENDED PCB LAYOUT



Below 14 pin product is without any "window."





Positions: 8, 10, 12, 14, 16, 18, 20, 24, 26, 28, 34, 40 & 44
A = .079 [2.00] x No. of Spaces
B = .079 [2.00] x No. of Spaces + .112 [2.85]
C = .079 [2.00] x No. of Spaces + .183 [4.65]

SPECIFICATIONS:
Material:
Insulator: Hi–temp thermoplastic, rated UL 94V–0
Insulator color: Black
Contacts: Brass
Plating:
Gold flash over nickel underplate overall.
Electrical:
Current rating: 1 Amp max
Contact resistance: 20 mohms max
Insulation resistance: 5000 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minut
Temperature Rating:
Operating temperature: –40°C to +105°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	7/30/08
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .079 [2.00] MOUNT BOX HEADER, DUAL ROW, RIGHT ANGLE, GOLD PLATED

SIZE	PART NO.	REV.
X	2MBHR-XX-HUA	A

REF: S00059T | SCALE: NTS | SHEET 1 OF 1