

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/29/21	


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





SPECIFICATIONS:
Material:
Insulator: Hi-temp thermoplastic, rated UL 94V-0
Insulator color: Black
Contacts: Brass
Plating:
Tin over Nickel underplate overall
Electrical:
Current rating: 2 Amp
Contact resistance: 20 mohms max
Insulation resistance: 1,000 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
-40°C to +105°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

PACKAGED ON TAPE & REEL
Positions: 01 thru 40
A = .079 [2.00] x No. of Positions - .008 [0.20]
B = .079 [2.00] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	OW	1/29/21
CHECKED	TL	1/29/21
APPROVED		

ADAM TECH
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .079 [2.00] SINGLE ROW PIN HEADER SURFACE MOUNT, TYPE B

SIZE	PART NO.	REV.
X	2PH1-XX-TA-SMT-B-L-PP-T/R	-

REF: S00111C | SCALE: NTS | SHEET 1 OF 1