Rev	AWO #	Description	Date	Appr
-		RELEASED	4/28/21	

APPROVED: _____

DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT



SPECIFICATIONS:
Material:
Insulator: Hi-temp thermoplastic, rated UL 94V-0
Insulator color: Black
Contacts: Copper Alloy
Plating:
Gold flash over Nickel underplate overall
Electrical:
Current rating: 2 Amp.
Contact resistance: 20 mohms max.
Insulation resistance: 1,000 Mohms min.
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
-40°C to +105°C
Environmental:
Lead free, RoHS compliant RoHS COMPLIANT

Positions: 04 thru 80
A = .079 [2.00] x No. of Positions per Row +.016 [0.40]
B = .079 [2.00] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

DRAWN	WX	4/28/21
CHECKED	TY	4/28/21
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH

ADAM TECH
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .079 x .079 DUAL ROW RECEPTACLE STRIP RIGHT ANGLE, HI-TEMP

SIZE	PART NO.	REV.
X	2RS2R-C-XX-G-.130-HT	X

REF: S00111C | SCALE: NTS | SHEET 1 OF 1