


Rev	AWO #	Description	Date	Appr
-		RELEASED	8/7/19	

APPROVED: _____


DATE: _____ TITLE: _____









RECOMMENDED PCB LAYOUT



08P~40P



06P



04P

SPECIFICATIONS:
Material:
Insulator: PA46, rated UL 94V-0
Insulator color: Beige
Contacts: Brass
Plating:
Matte Tin over copper underplate overall
Electrical:
Voltage rating: 250 VAC/DC (rms)
Current rating: 3A
Contact resistance: 10 mohms max.
Insulation resistance: 1,000 Mohms min.
Dielectric withstanding voltage: 800 VAC for 1 minute
Mechanical:
Wire range: 28~22 AWG
Temperature Rating:
Operating temperature: -25°C to +85°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

Positions: 08 thru 40
A = .079 [2.00] x No. of Positions + .075 [1.90]
B = .079 [2.00] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	LH	8/7/19
CHECKED	TY	8/7/19
APPROVED		

ADAM TECH
INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .079 [2.00] DOUBLE ROW, SHROUDED HEADER , RIGHT ANGLE, PCB, MATTE TIN PLATED

SIZE	PART NO.	REV.
X	2SHD-C3-XX-MTR	-

REF:	SCALE:	SHEET
S00111C	NTS	1 OF 1