


APPROVED: _____


DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	7/18/16	
A		UPDATED DIM.	3/7/17	HR/CT










RECOMMENDED PCB LAYOUT
BOTTOM VIEW



SPECIFICATIONS:
Material:
Insulator: PBT, rated UL 94V–0
Insulator color: Black
Terminal: Phosphor Bronze
Spring: Phosphor Bronze
Top Lead & Spring Lead: Brass
Plating:
Silver over Copper underplate overall
Electrical:
Contact resistance: 30 mohms max
Insulation resistance: 100 Mohms min @ 500 VDC
Dielectric withstanding voltage: 500 V for 1 minute
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	7/18/16
CHECKED	CT	7/18/16
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: 3.5MM STACKED DUAL STEREO JACK FULLY SHIELDED

SIZE	PART NO.	REV.
X	ASJ-DP-38-3	A

REF:	SCALE:	SHEET
S00062T	NTS	1 OF 1