


APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_  
 CUSTOM CABLE ASSEMBLIES ARE NON-CANCELLABLE/NON-RETURNABLE

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/9/19	
A		ADDED 5P, 8P OPTION	9/23/20	AY/RC
B		UPDATE SPEC.	3/3/21	LH/RC

(Number of Conductors) N	4P	5P	8P	12P	16P	24P	30P	36P	40P
(Pitch) P	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08	1.00 ± 0.08
(Total Pitch) Pt	3.00 ± 0.10	4.00 ± 0.10	7.00 ± 0.10	11.0 ± 0.10	15.0 ± 0.10	23.00 ± 0.10	29.00 ± 0.10	35.00 ± 0.10	39.00 ± 0.10
(Total Length) L	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00	101.6 ± 2.00
(Film Length) IL	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00	93.60 ± 2.00
(Margin Width) M	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10	1.00 ± 0.10
(Total Width) W	5.00 ± 0.12	6.00 ± 0.12	9.00 ± 0.12	13.00 ± 0.12	17.00 ± 0.12	25.00 ± 0.12	31.00 ± 0.12	37.00 ± 0.12	41.00 ± 0.12
(Strip Length) S1	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00
(Strip Length) S2	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00	4.00 ± 1.00
(Stiffener) B1	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00
(Stiffener) B2	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00	8.00 ± 2.00
(Slanting) A1	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30
(Slanting) A2	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30	≤ 0.30
(Terminal thickness) t	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03
(Thickness) T	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03	0.12 ± 0.03



(Number of Conductors)  
 CA-DK10-XX-101.6-A-44-88  
 T  
 04  
 05  
 08  
 12  
 16  
 24  
 30  
 36  
 40

SPECIFICATIONS:  
 Material:  
 Insulator: PET, color White.  
 Support Tape: PET, color Blue.  
 UL Style: AWM 2743, 105°C, 90V VW-1  
 Plating:  
 Conductor: Tin plated Copper Flat plated.  
 Environmental:  
 Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED  
 ALL DIMENSIONS ARE MILLIMETERS  
 TOLERANCES: EXCEPT AS NOTED  
 SEE CHART

APPROVALS		DATE
DRAWN	AY	1/9/19
CHECKED	AC	1/9/19
APPROVED		

909 Rahway Avenue,  
 Union, NJ 07083  
 Phone: 908-687-5000  
 Fax: 908-687-5710

**ADAM TECH**

TITLE: FLAT FLEXIBLE CABLE, .039" [1MM] PITCH  
 SAME SIDE CONTACTS, TOTAL LENGTH 101.6MM

SIZE	PART NO.	REV.
X	CA-DK10-XX-101.6-A-44-88	B

REF: S00187C SCALE: NTS SHEET 1 OF 1

6

5

4

3

2

1

6

5

4

3

2

1