


Rev	AWO #	Description	Date	Appr
-		RELEASED	05/03/12	


APPROVED: _____

DATE: _____ TITLE: _____









RECOMMENDED PCB LAYOUT

SPECIFICATIONS:
Material:
Insulator: PBT, rated UL 94V-0
Insulator color: Black
Contacts: Brass
Plating:
15u" Gold over Nickel underplate on mating area,
Tin over Copper underplate on tails
Electrical:
Operating voltage: 250 VAC max
Current rating: 2.5 Amps max
Insulation resistance: 1,000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 600 VAC for 1 minute
Temperature Rating:
Operating temperature: -25°C to +85°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

Positions: 02 thru 18
A = .100 [2.54] x No. of Positions + .100 [2.54]
B = .100 [2.54] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	TW	05/03/12
CHECKED	AY	05/03/12
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .100 [2.54] LATCHING HEADER, PCB
RIGHT ANGLE, 15u" SEL-GOLD PLATED

SIZE	PART NO.	REV.
X	CDR-XX-SGR-15	-

REF: S00016T | SCALE: NTS | SHEET 1 OF 1