


APPROVED: _____


DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/31/06	
A		UPDATED POSITIONS	8/23/06	
B		UPDATE DRAWING	1/5/18	AY/RC1









Positions: 04 thru 74, 80, 86, 92, 98, 100
A = .100 [2.54] x No. of Spaces
B = A + .200 [5.08]
C = A + .360 [9.14]
D = A + .277 [7.04]

SPECIFICATIONS:
Material:
Insulator: PBT, Glass reinforced, rated UL 94V-0
Insulator color: Black
Contacts: Copper Alloy
Plating:
30u" Gold over Nickel underplate on contact area,
Tin over Nickel underplate on PCB tails
Electrical:
Current rating: 3A.
Contact resistance: 20 mohms max.
Insulation resistance: 5,000 Mohms min @ 500 VDC.
Dielectric withstanding voltage: 1000 VAC for 1 minute
Temperature Rating:
Operating temperature: -55°C to +85°C
Environmental:
Lead free, RoHS complaint

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	LFJ	3/31/06
CHECKED		
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: CARD EDGE CONNECTOR, VERTICAL, PCB 30u" SEL GOLD PLATED

SIZE	PART NO.	REV.
X	CE-XX-U-30	B

REF: S00245T | SCALE: NTS | SHEET 1 OF 1