


APPROVED: _____


DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
-		RELEASED	2/17/10	
A		REVISED SHAPE	3/10/10	












RECOMMENDED P.C.B. LAYOUT



SPECIFICATIONS:

Material:
Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
Insulator color: Beige
Contacts: Brass

Plating:
15u" Gold over Nickel underplate on contact area,
Tin over Copper underplate on SMT tails

Electrical:
Operating voltage: 100 VAC max
Current rating: 0.5 Amps max
Contact resistance: 40 mohms
Insulation resistance: 1000 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minute

iMechanical:
Life Cycles: 10K mating cycles min.
Mating Force: 28.8N max.
Unmating Force: 4.9N Min. / 24.5N Max.

Temperature Rating:
Operating temperature: -20°C to +90°C

Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

POWER	5.00mm	1,13,38,50
GENERAL	4.25mm	all other pins
DETECT	3.50mm	25,26
Pin type	Interface Dim. L	Pin No.

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	8/24/07
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: COMPACT FLASH HEADER, TYPE 1, SURFACE MOUNT

SIZE	PART NO.	REV.
X	CF1-50-A-SG-15	A

REF: S00009T | SCALE: NTS | SHEET 1 OF 1