


Rev	AWO #	Description	Date	Appr
-		RELEASED	11/27/14	


APPROVED: _____

DATE: _____ TITLE: _____









RECOMMENDED PCB LAYOUT

ADAM TECH PART NO.	CURRENT RATING	DIMENSION A	B
D7W2-SLP-6-1	40 AMPS	ø.148 [3.75]	ø.165 [4.20]
D7W2-SLP-5-1	30 AMPS	ø.126 [3.20]	ø.144 [3.65]
D7W2-SLP-4-1	20 AMPS	ø.110 [2.80]	ø.129 [3.28]
D7W2-SLP-3-1	10 AMPS	ø.067 [1.70]	ø.087 [2.20]

SPECIFICATIONS:

Material:

Insulator: Thermoplastic, glass reinforced, rated UL 94V-0

Insulator color: Black

Contacts: Brass

Shell: Steel, Tin plated

Plating:

Gold flash over Nickel underplate overall

Electrical:

Current rating: 10 - 40 Amps max (Power Contact)
5 Amps max (Signal Contact)

Contact resistance: 10 mohms max

Insulation resistance: 5,000 Mohms min

Dielectric withstanding voltage: 1,000 VAC for 1 minute

Temperature Rating:

Operating temperature: -55°C to +125°C

Environmental:

Lead free, RoHS compliant

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	11/27/14
CHECKED	GC	11/27/14
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: D-SUB POWER SOCKET, D7W2, FEMALE, STRAIGHT PCB,

SIZE	PART NO.	REV.
X	D7W2-SLP-X-1	-

REF: S00019T | SCALE: NTS | SHEET 1 OF 1