

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/11/11	
A		REVISED PIN DIM.	02/16/12	
B		UPDATE DRAWING	8/26/20	AY/TL


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





SPECIFICATIONS:

Material:
Insulator: Thermoplastic Polyester Glass Filled, rated UL 94V–0
Contacts: Copper Alloy
Lock: Copper Alloy

Plating:
X Gold over Nickel underplate on contact area,
Tin over Copper underplate on solder tails.
(See chart for thickness)

Electrical:
Current rating: 2 Amp
Contact resistance: 20 mohms max @ DC 100mA
Insulation resistance: 1000 Mohms min@ DC 500V
Dielectric withstanding voltage: 1000 VAC for 1 minute

Temperature Rating:
Operating temperature: –55°C to +125°C

Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

"X"	PLATING	CLASS
1	30 u" Gold	1
2	15 u" Gold	2
3	Gold Flash	3

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MM [INCHES]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	1/11/11
CHECKED	JL	1/11/11
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: DIN TYPE HALF B, 20 PINS LOADED
2 ROW STRAIGHT, ROW A & B LOADED

SIZE	PART NO.	REV.
X	DIN-20FS-S22-A1CX-BL	B

REF: S00058T | SCALE: NTS | SHEET 1 OF 1