


APPROVED: _____

DATE: _____ TITLE: _____



ESM-XXXXA02-XXX


Universal model: 120A, 090A

Key Options

Housing Color:
O=Orange
B=Black

laser marking
Orange is positive: (+)
black is negative: (-)

laser marking
See Chart



SPECIFICATIONS:

Connector:

Housing: PA66, Glass reinforced, rated UL 94V-0

Housing color: Orange/Black

Cap: PA66, Glass reinforced, rated UL 94V-0

Top: PA66, Glass reinforced, rated UL 94V-0

Waterproof ring: Silicone

Contact: Pure Red Copper, Silver plated Surface

Spring: SUS301

Electrical:

Voltage rating: 1000V DC

Current rating: 90A/120A

Contact resistance: 0.5 mohms max

Insulation resistance: 5,000 Mohms min

Dielectric withstanding voltage: 3,800V DC

Mechanical:

Durability: 500 cycles

Overvoltage Category/Pollution Degree: CATIII/3

Temperature Rating: -40°C to +125°C

Environmental:


Waterproof: IP67 (Mating)

Lead free, RoHS compliant



Note: Connector packaged in tray
Nut and Seal Ring packaged
separately in poly bag

Rev	AWO #	Description	Date	Appr
-		RELEASED	12/18/23	
A		UPDATE DRAWING	7/26/24	LH/RC
B		UPDATE DRAWING	8/6/24	LH/RC
C		ADDED SPEC.	8/21/24	LH/RL
D		UPDATE DRAWING	12/13/24	LW1/FH
E		UPDATE DRAWING	1/16/25	LW1/MC
F		ADDED PAGE 3, 4 (170A SPEC.)	9/24/25	LH/TW
G		REMOVED PAGE 3, 4 (170A SPEC.)	7/23/26	LH/RC



Suitable wire gauge

Specification		Universal model
AWG American wire gauge	Wire standard: 4 AWG	120A
	Strand outer diameter: $\phi 6.47$ Max	
	O.D (Outside Diameter): $\phi 9.50$ Max	
International Wire Gauge	Wire standard: 25mm ²	090A
	Strand outer diameter: $\phi 7.20$ Max	
	O.D (Outside Diameter): $\phi 9.80$ Max	
AWG American wire gauge	Wire standard: 6 AWG	090A
	Strand outer diameter: $\phi 5.20$ Max	
	O.D (Outside Diameter): $\phi 8.50$ Max	
International Wire Gauge	Wire standard: 16mm ²	090A
	Strand outer diameter: $\phi 5.80$ Max	
	O.D (Outside Diameter): $\phi 8.00$ Max	

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

.X	± .10	HOLES ϕ .X	± .10
INCHES .XX	± .020	ϕ .XX	± .015
.XXX	± .015	ϕ .XXX	± .010

DRAWN	WX	12/18/23
CHECKED	CK	12/18/23
APPROVED		

CONFIDENTIAL AND PROPRIETARY

© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE

ENERGY STORAGE CONNECTOR, MALE

SIZE
X

PART NO.

ESM-XXXXA02-XXX

REV.
G


REF: S00005C

SCALE: NTS


SHEET 1 OF 6

APPROVED: _____


DATE: _____ TITLE: _____



Screw Nut
(Packaged separately in poly bag)




Seal Ring For 6AWG&16mm²
(Packaged separately in poly bag)



Seal Ring For 4AWG&25mm²
(Packaged separately in poly bag)

Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 6 FOR REVISION				



Wire range	Current rating	DIM "D"
6AWG&16mm ²	90A	.236 [6.00]
4AWG&25mm ²	120A	.276 [7.00]



Note: Connector packaged in tray
Nut and Seal Ring packaged poly bag separately

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED			<div>ADAM TECH</div>	909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 adam-tech.com	
.X ± .10	HOLES Ø.X ± .10				
INCHES .XX ± .020	HOLES Ø.XX ± .015				
.XXX ± .015	HOLES Ø.XXX ± .010				
DRAWN	WX	12/18/23	TITLE ENERGY STORAGE CONNECTOR, MALE		
CHECKED	CK	12/18/23			
APPROVED					
CONFIDENTIAL AND PROPRIETARY © Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other Intellectual property rights worldwide.			SIZE X	PART NO. ESM-XXXA02-XXX	REV G
			REF: S00005C	SCALE: NTS	SHEET 2 OF 6

APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 6 FOR REVISION				



ESM-XXXXA02-XXX


Universal model: 170A, 200A, 250A

KEY Options

Housing Color:
O=Orange
B=Black

laser marking
Orange is positive: (+)
black is negative: (-)

laser marking
See Chart



Suitable wire gauge

Specification		Universal model
AWG American wire gauge	Wire standard: 2/0 AWG	250A
	Strand outer diameter: $\phi 11.6$ Max	
	O.D (Outside Diameter): $\phi 15.1$ Max	
International Wire Gauge	Wire standard: 70mm ²	200A
	Strand outer diameter: $\phi 12.2$ Max	
	O.D (Outside Diameter): $\phi 15.5$ Max	
AWG American wire gauge	Wire standard: 1/0 AWG	200A
	Strand outer diameter: $\phi 10.3$ Max	
	O.D (Outside Diameter): $\phi 14.2$ Max	
International Wire Gauge	Wire standard: 50mm ²	200A
	Strand outer diameter: $\phi 10.2$ Max	
	O.D (Outside Diameter): $\phi 13.5$ Max	

SPECIFICATIONS:

Connector:

Housing: PA66, Glass reinforced, rated UL 94V-0

Housing color: Orange/Black

Cap: PA66, Glass reinforced, rated UL 94V-0

Top: PA66, Glass reinforced, rated UL 94V-0

Waterproof ring: Silicone

Contact: Pure Red Copper, Silver plated Surface

Spring: SUS301

Electrical:

Voltage rating: 1500V DC

Current rating: 200A/250A

Contact resistance: 0.5 mohms max

Insulation resistance: 5,000 Mohms min

Dielectric withstanding voltage: 6,800V DC

Mechanical:

Durability: 500 cycles

Overvoltage Category/Pollution Degree: CATIII/3

Temperature Rating: -40°C to +125°C

Environmental:

Waterproof: IP67 (Mating)

Lead free, RoHS compliant




Note: Connector packaged in tray
Nut and Seal Ring packaged
separately in poly bag

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED				<div>ADAM TECH</div> <div>909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 adam-tech.com</div>	
.X ± .10 .XX ± .020 .XXX ± .015		HOLES Ø.X ± .10 Ø.XX ± .015 Ø.XXX ± .010			
DRAWN		WX 12/18/23			
CHECKED		CK 12/18/23			
APPROVED					
<div>CONFIDENTIAL AND PROPRIETARY</div> <div>© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.</div>					
SIZE X		PART NO. ESM-XXXXA02-XXX		REV. G	
REF: S00005C		SCALE: NTS		SHEET 3 OF 6	

APPROVED: _____


DATE: _____ TITLE: _____




Screw Nut

Wire range	Current rating	DIM "D"
1/0AWG/50mm ²	200A	.551 [14.00]
2/0AWG&70mm ²	250A	.622 [15.80]

(Packaged separately in poly bag)




Seal Ring For 1/0AWG/50mm² (200A)
(Packaged separately in poly bag)




Seal Ring For 2/0AWG&70mm² (250A)
(Packaged separately in poly bag)

Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 6 FOR REVISION				



Wire range	Current rating	DIM "D"
1/0AWG/50mm ²	200A	.531 [13.50]
2/0AWG&70mm ²	250A	.610 [15.50]

Note: Connector packaged in tray
Nut and Seal Ring packaged poly bag separately



Plug Bushing For 2/0AWG&70mm² (250A)
(Packaged separately in poly bag)

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

.X	± .10	Ø.X	± .10
INCHES .XX	± .020	HOLES Ø.XX	± .015
.XXX	± .015	Ø.XXX	± .010

DRAWN	WX	12/18/23
CHECKED	CK	12/18/23
APPROVED		

CONFIDENTIAL AND PROPRIETARY
© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE
ENERGY STORAGE CONNECTOR, MALE


SIZE X	PART NO. ESM-XXXXA02-XXX	REV. G
-----------	-----------------------------	-----------

REF: S00005C SCALE: NTS SHEET 4 OF 6



APPROVED: _____

DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 6 FOR REVISION				



ESM-XXXXA02-XXX
Universal model: 350A, 300A
Key Options
Housing Color:
O=Orange
B=Black



laser marking
Orange is positive: (+)
black is negative: (-)



laser marking
See Chart

Suitable wire gauge

Specification		Universal model
AWG American wire gauge	Wire standard: 4/0 AWG	350A
	Strand outer diameter: $\phi 14.7$ Max	
	O.D (Outside Diameter): $\phi 18.5$ Max	
		300A
International Wire Gauge	Wire standard: 95mm ²	
	Strand outer diameter: $\phi 14.2$ Max	
	O.D (Outside Diameter): $\phi 17.6$ Max	

SPECIFICATIONS:

Connector:

Housing: PA66, Glass reinforced, rated UL 94V-0

Housing color: Orange/Black

Cap: PA66, Glass reinforced, rated UL 94V-0

Top: PA66, Glass reinforced, rated UL 94V-0

Waterproof ring: Silicone

Contact: Pure Red Copper, Silver plated Surface

Spring: SUS301

Electrical:

Voltage rating: 1500V DC

Current rating: 300A/350A

Contact resistance: 0.5 mohms max

Insulation resistance: 5,000 Mohms min

Dielectric withstanding voltage: 6,800V DC

Mechanical:

Durability: 500 cycles

Overvoltage Category/Pollution Degree: CATIII/3

Temperature Rating: -40°C to $+125^\circ\text{C}$

Environmental:

Waterproof: IP67 (Mating)

Lead free, RoHS compliant



Note: Connector packaged in tray
Nut and Seal Ring packaged
separately in poly bag



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED					
.X	$\pm .10$	HOLES $\phi .X$	$\pm .10$		
INCHES .XX	$\pm .020$	HOLES $\phi .XX$	$\pm .015$		
.XXX	$\pm .015$	HOLES $\phi .XXX$	$\pm .010$		
DRAWN	WX	12/18/23			
CHECKED	CK	12/18/23			
APPROVED					
CONFIDENTIAL AND PROPRIETARY © Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.					

ADAM
TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE

ENERGY STORAGE CONNECTOR, MALE

SIZE
X

PART NO.

ESM-XXXXA02-XXX

REV.
G

REF: S00005C

SCALE: NTS

SHEET 5 OF 6

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev


AWO #

Description


Date

Appr


SEE SHT 1 OF 6 FOR REVISION



Screw Nut For 4/0AWG (350A)&95mm² (300A)
(Packaged separately in poly bag)



Note: Connector packaged in tray
Nut and Seal Ring packaged poly bag separately



Seal Ring For 4/0AWG (350A)&95mm² (300A)
(Packaged separately in poly bag)

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS
ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

.X	± .10	Ø.X	± .10
INCHES .XX	± .020	HOLES Ø.XX	± .015
.XXX	± .015	Ø.XXX	± .010

DRAWN

WX

12/18/23

CHECKED

CK

12/18/23

APPROVED

CONFIDENTIAL AND PROPRIETARY

© Adam Tech. All rights reserved. This document contains confidential and proprietary information belonging to Adam Tech. It is provided solely for design and reference purposes by authorized parties. Any reproduction, distribution, display, or disclosure to third parties, in whole or in part, without the prior written consent of Adam Tech, is strictly prohibited. Adam Tech retains all rights, including copyright, trademark, trade secret, and all other intellectual property rights worldwide.

**ADAM
TECH**

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
adam-tech.com

TITLE

ENERGY STORAGE CONNECTOR, MALE

SIZE
X

PART NO.

ESM-XXXXA02-XXX

REV.
G

REF: S00005C

SCALE: NTS

SHEET 6 OF 6