


Rev	AWO #	Description	Date	Appr
-	7718	RELEASED	4/18/07	

APPROVED: _____


DATE: _____ TITLE: _____








RECOMMENDED P.C.B. LAYOUT





SPECIFICATIONS:

Material:
Insulator: PBT, glass reinforced, rated UL 94V–0
Insulator color: Black
Contacts: Phosphor Bronze
Plating:
Tin over Nickel underplate overall

Electrical:
Operating voltage: 250 VAC max
Current rating: 1 Amp max
Contact resistance: 15 mohms max
Insulation resistance: 1,000 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minute

Environmental:
Temperature Rating:
Operating temperature: –40°C to +105°C
Lead free, RoHS compliant
Recommended soldering temp: 235°C for 5 seconds

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	BW	4/18/07
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: IDC TRANSITION PLUG
26 POSITION W/ KINKED PINS

SIZE	PART NO.	REV.
X	FTR-26-T-K01-02-25-26	-

REF: | SCALE: NTS | SHEET 1 OF 1