





APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/24/05	
A		REDRAWN	12/6/11	
B		UPDATED DRAWING	7/23/20	OW/BL
C		UPDATED SPEC.	6/28/23	LH/KL



SPECIFICATIONS:

Material:

Insulator: Hi-Temp Thermoplastic, rated UL 94V-0

Insulator color: Black

Contacts: Brass

Plating:

Gold flash over Nickel underplate on contact area,

Tin over Copper underplate on SMT tails

Electrical:

Current rating: 1 Amp

Contact resistance: 10 mohms max @ DC 100mA

Insulation resistance: 5,000 Mohms min @ DC 500V

Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:

Operating temperature: -40°C to +105°C

Environmental:

Lead free, RoHS compliant



Positions: 10, 12, 14, 16, 20, 24, 26, 28, 30, 34, 40, 44, 50, 60, 64, 68, 80

A= .050 [1.27] x No. of Space

B= .050 [1.27] x No. of Space per Row + .237 [6.02]

C= .050 [1.27] x No. of Space per Row + .298 [7.57]

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS		DATE
DRAWN	SS	3/24/05
CHECKED		
APPROVED		

ADAM
TECH
INTERCONNECTS

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE			
.050" x .050" BOX HEADER VERTICAL MOUNT, SURFACE MOUNT			
SIZE X	PART NO. HBHR-B-XX-VSG-SMT	REV. C	
REF: S00059T	SCALE: NTS	SHEET 1 OF 1	