

Rev	AWO #	Description	Date	Appr
-		RELEASED	8/15/18	


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





SPECIFICATIONS:
Material:
Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
Insulator color: Black
Contacts: Brass
Plating:
Matte Tin over Copper underplate overall
Electrical:
Current rating: 1 Amp
Contact resistance: 20 mohms max @ DC 100 mA
Insulation resistance: 5,000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

Positions: 04 thru 100
A = .050 [1.27] x No. of Positions per Row - .008 [0.20]
B = .050 [1.27] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	8/15/18
CHECKED	RT	8/15/18
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .050 [1.27] DUAL ROW PIN HEADER, SMT
MATTE TIN PLATED

SIZE	PART NO.	REV.
X	HPH2-A-XX-MT-SMT-.157	-

REF: S00059T | SCALE: NTS | SHEET 1 OF 1