


Rev	AWO #	Description	Date	Appr
-		RELEASED	12/11/08	


APPROVED: _____

DATE: _____ TITLE: _____











PINOUT



TOP VIEW



PCB LAYOUT
(BOTTOM VIEW)

SPECIFICATIONS:
Material:
Insulator: PBT, glass filled, rated UL 94V-0
Insulator color: Black
Contacts: Phosphor Bronze
Shield: Copper Alloy, Nickel plated
Plating:
Gold over Nickel underplate on contact area, Tin over Copper underplate on tails
Electrical:
Operating voltage: 100 VAC/12 VDC max.
Current rating: 1 Amp max./2 Amps max.
Contact resistance: 20 mohms max. initial
Insulation resistance: 500 Mohms min.
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: -25°C to +70°C
Environmental:
Lead free, RoHS compliant.
Recommended soldering temp: 235°C for 5 sec.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	12/11/08
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
MINI DIN JACK, RIGHT ANGLE, SHIELDED

SIZE	PART NO.	REV.
X	MDJ-008-S-FY	-

REF: | SCALE: NTS | SHEET 1 OF 1