

Rev	AWO #	Description	Date	Appr
-		RELEASED	12/3/19	


APPROVED: _____


DATE: _____ TITLE: _____



RECOMMENDED PCB LAYOUT
TOP VIEW, 1.6mm PCB THICKNESS







SPECIFICATIONS:
Material:
Insulator: PBT, rated UL 94V–0
Insulator color: Black
Contacts: Phosphor Bronze
Plating:
Round contact
Gold over Nickel underplate overall
Flat contact
Gold over Nickel underplate on contact area,
Tin over Nickel underplate on solder tails
Electrical:
Voltage rating: 150 VAC max
Current rating: 1.5 Amps max
Contact Resistance: 20 mohms max
Insulation resistance: 1,000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1,000 VAC/DC for 1 minut
Temperature Rating:
Operating temperature: –40°C to +85°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

PACKAGED ON PLASTIC TUBE

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	12/3/19
CHECKED	LW	12/3/19
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: MODULAR TELEPHONE JACK, 6P6C, VERTICAL THRU-HOLE PCB, SPLIT PEG, PLASTIC TUBE

SIZE	PART NO.	REV.
X	MTJ-66KBX1-TH-SP-PT	-

REF: S00005C | SCALE: NTS | SHEET 1 OF 1