

Rev	AWO #	Description	Date	Appr
-		RELEASED	10/20/15	


APPROVED: _____


DATE: _____ TITLE: _____



RECOMMENDED PCB LAYOUT







X	PLATING
0	15 µin Gold
1	30 µin Gold
2	50 µIn Gold

SPECIFICATIONS:

Material:
Insulator: Thermoplastic, rated UL 94V-0
Insulator Color: Black
Contacts: Copper Alloy
Shield: Brass, Nickel plated
Plating:
Round contact
Gold over Nickel underplate overall
Flat contact
Gold over Nickel underplate on contact area,
Tin over Nickel underplate on solder tails
(See chart for thickness)
Electrical:
Operating voltage: 150 VAC max
Contact Resistance: 20 mohms max
Insulation resistance: 500 Mohms min
Dielectric withstanding voltage: 2,250 VDC for 1 minute
Temperature Rating:
Operating temperature: 0°C to +70°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	10/20/15
CHECKED	MW	10/20/15
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: MODULAR TELEPHONE JACK, 1 PORT, 8P8C W/ LED1 YELLOW, LED2 GREEN


SIZE	PART NO.	REV.
X	MTJ-88TUX1-FSD-VLG-M21C	-


REF: S00005C | SCALE: NTS | SHEET 1 OF 2

Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 2 FOR REVISION				

APPROVED: _____

DATE: _____ TITLE: _____





LED2	Green	LED1	Yellow
P11	−	P13	−
P12	+	P14	+

ELECTRICAL SPECIFICATIONS:

1. Turns Ratio @100KHz: (P1 ~ P2) : (J1 ~ J2) 1:1 ±5%
   (P3 ~ P4) : (J3 ~ J6) 1:1 ±5%
   (P7 ~ P8) : (J4 ~ J5) 1:1 ±5%
   (P9 ~ P10) : (J7 ~ J8) 1:1 ±5%
2. Primary Inductance: 350uH Min. @100KHz ,0.1V 8mA DC Bias
3. DC Resistance: 1.2 Ohms Max.
4. Insertion Loss: 1~100MHZ : −1.0dB Max.
   100~125MHZ : −1.2dB Max.
5. Return Loss: 1~40MHZ: −16dB Min.
   40~60MHZ: −12dB Min.
   60~80MHZ: −10dB Min.
   80~100MHZ: −8dB Min.
6. Cross Talk: 1~100MHZ: −30dB Min.
7. Common to Common mode Attenuation: 1~100MHZ: −30dB Min.
8. Isolation: PHY Side to Line Side : 2250VDC

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	10/20/15
CHECKED	MW	10/20/15
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: MODULAR TELEPHONE JACK, 1 PORT, 8P8C W/ LED1 YELLOW, LED2 GREEN

SIZE	PART NO.	REV.
X	MTJ-88TUX1-FSD-VLG-M21C	-

REF: S00005C | SCALE: NTS | SHEET 2 OF 2