

APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/4/20	
A		UPDATE PACKING	4/10/20	AY/BL





RECOMMENDED PCB LAYOUT

PACKAGED ON TAPE & REEL

SPECIFICATIONS:
Material:
Insulator: PBT, rated UL 94V–0
Insulator color: Black
Contacts: Phosphor Bronze
Cantacts Plating:
Round contact
Gold over Nickel underplate overall
Flat contact
Gold over Nickel underplate on contact area,
Tin over Nickel underplate on solder tails
Electrical:
Voltage rating: 150 VAC Rms
Current rating: 1.5 Amps
Contact Resistance: 20 mohms max
Insulation resistance: 1,000 Mohms min @ 500 VDC
Dielectric withstanding voltage:
Contact to Contact: 1,000 VDC or AC Peak for 1 minute
Contact to Screen and Test panel: 1,500 VDC or AC Peak for 1 minute
Temperature Rating:
Operating temperature: –40°C to +85°C
Environmental:
Lead free, RoHS Compliant

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	3/4/20
CHECKED	BL	3/4/20
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: MODULAR TELEPHONE JACK, GANGED 8P8C

SIZE	PART NO.	REV.
X	MTJG-2-88ARX1-T/R	A


REF: S00005C | SCALE: NTS | SHEET 1 OF 2


Rev	AWO #	Description	Date	Appr
SEE SHT 1 OF 2 FOR REVISION				

APPROVED: _____


DATE: _____ TITLE: _____

1 REEL/ 160PCS







1 CARTON/ 4 BOX/ 8 REEL/ 1280 PCS




2 REEL/ 1 BOX









DRYER 2 PCS







PULL OUT DIRECTION

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS

APPROVALS		DATE
DRAWN	AY	3/4/20
CHECKED	BL	3/4/20
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: MODULAR TELEPHONE JACK, GANGED 8P8C

SIZE	PART NO.	REV.
X	MTJG-2-88ARX1-T/R	A

REF:	SCALE:	SHEET
S00005C	NTS	2 OF 2