

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/24/14	


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





SPECIFICATIONS:
Material:
Insulator: Hi-Temp Thermoplastic, rated UL 94V-0
Insulator color: Black
Contacts: Brass
Plating:
15u" Gold over Nickel underplate on contact area, Tin over Copper underplate on tails
Electrical:
Current rating: 3 Amps max
Contact resistance: 20 mohms max
Insulation resistance: 5,000 Mohms min @ 500 VDC
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	HR	1/24/14
CHECKED	SL	1/24/14
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
.100 [2.54] DUAL ROW PIN HEADER, RIGHT ANGLE
15u" SELECTIVE GOLD PLATED, HI-TEMP

SIZE	PART NO.	REV.
X	PH2RA-06-VA-X03-HT	-

REF:	SCALE:	SHEET
S00059T	NTS	1 OF 1