


APPROVED: _____


DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/22/04	
A		REVISED DIM.	7/3/13	









A = .100 [2.54] X No. of Positions
B = .100 [2.54] X No. of Spaces

SPECIFICATIONS:
Material:
Insulator: PBT, glass reinforced, rated UL 94V-0
Insulator color: Black
Contacts: Phosphor Bronze
Plating:
Gold Flash over Nickel underplate on contact area, tin over Copper underplate on solder tails
Electrical:
Current rating: 3 Amps max
Contact rsistance: 20 mohms max
Insulation resistance: 5000 Mohms min @ 500 VDC
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	11/22/04
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .100 [2.54] RECEPTACLE STRIP, SINGLE ROW, .268 [6.80] BODY HEIGHT

SIZE	PART NO.	REV.
X	RS1B-XX-SG	A

REF: | SCALE: NTS | SHEET 1 OF 1