

DC AXIAL FAN 40x40x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
Lead Wire: UL Type #28 AWG
Weight: 11 g **Packing:** 400PCS/CTN



ES **IP** **SF**



DC Axial Fans

Model Number	Voltage (VDC)	Op. Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD4010B05W3-81	5	4.5~6.0	5.50	1.70	19.20	4,000	90	0.45	B,S	①
FD4010B05W5-81	5	4.5~6.0	6.80	2.50	25.10	5,000	130	0.65	B,S	②
FD4010B05W7-81	5	4.5~6.0	8.10	3.70	28.60	6,000	250	1.25	B,S	③
FD4010B12W3-81	12	9.0~13.8	5.50	1.7	19.20	4,000	50	0.60	B,S	①
FD4010B12W5-81	12	6.0~13.8	6.80	2.50	25.10	5,000	80	0.96	B,S	②
FD4010B12W7-81	12	6.0~13.8	8.10	3.70	28.60	6,000	120	1.44	B,S	③

• For "Sleeve" bearing version, change the "B" in the model number to "S".

Specifications are subject to change without notice

