

# DC AXIAL FAN 60x60x20mm



**Housing/Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 10MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 5mA max, 500VAC/min between bare wire and frame  
**Operation Temperature:** -20°C~70°C(Humidity 15%-90%RH)  
**Storage Temperature:** -40°C~85°C(Humidity 15%-90%RH)  
**Lead Wire:** UL Type #26 AWG  
**Weight:** 43 g      **Packing:** 200PCS/CTN



ES

IP

SF

DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6020B05W1-81	5	4.0~5.5	13.60	2.00	20.70	2,900	110	0.55	B,S	②
FD6020B05W3-81	5	4.0~5.5	16.60	2.90	26.60	3,500	150	0.75	B,S	③
FD6020B05W5-81	5	4.0~5.5	19.50	3.70	31.00	4,100	210	1.05	B,S	④
FD6020B12W00-81	12	8.0~13.8	11.00	1.30	13.30	2,300	50	0.60	B,S	①
FD6020B12W1-81	12	8.0~13.8	13.60	2.00	20.70	2,900	80	0.96	B,S	②
FD6020B12W3-81	12	6.0~13.8	16.60	2.90	26.60	3,500	110	1.32	B,S	③
FD6020B12W5-81	12	6.0~13.8	19.50	3.70	31.00	4,100	150	1.80	B,S	④
FD6020B24W5-81	24	12.0~27.6	19.50	3.70	31.00	4,100	100	2.40	B,S	④

• For "Sleeve" bearing version, change the "B" in the model number to "S".

Specifications are subject to change without notice

