

DC BLOWER 50x50x15mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 24 g Packing: 200PCS/CTN



ES IP SF



DC Blowers

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD5015B05W1-81	5	4.0~5.5	1.60	2.20	17.20	2,500	40	0.20	B	①
FBD5015B05W3-81	5	4.0~5.5	2.40	5.10	26.60	3,500	70	0.35	B	②
FBD5015B05W5-81	5	4.0~5.5	3.10	10.40	34.50	4,500	140	0.70	B	③
FBD5015B05W7-81	5	4.0~5.5	3.80	16.80	38.90	5,500	190	0.95	B	④
FBD5015B05W9-81	5	4.0~5.5	4.30	23.60	43.30	6,500	300	1.50	B	⑤
FBD5015B12W1-81	12	9.0~13.8	1.60	2.20	17.20	2,500	30	0.36	B	①
FBD5015B12W3-81	12	9.0~13.8	2.40	5.10	26.20	3,500	40	0.48	B	②
FBD5015B12W5-81	12	9.0~13.8	3.10	10.40	34.50	4,500	60	0.72	B	③
FBD5015B12W7-81	12	6.0~13.8	3.80	16.80	38.90	5,500	110	1.32	B	④
FBD5015B12W9-81	12	6.0~13.8	4.30	23.60	43.30	6,500	210	2.52	B	⑤
FBD5015B12W10-81	12	6.0~13.2	5.00	33.60	46.80	7,500	250	3.00	B	⑥

Specifications are subject to change without notice

