

# DC BLOWER 75x75x30mm



Housing/Blade: Thermoplastic PBT, UL 94V-0  
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame  
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)  
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)  
 Lead Wire: UL Type #26 AWG  
 Weight: 61 g      Packing: 100PCS/CTN



ES IP SF

Model Number		Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD7530B12W2-81	★	12	6.0~13.8	5.30	1.60	18.70	1,500	90	1.08	B	①
FBD7530B12W3-81	★	12	6.0~13.8	7.00	3.60	27.10	2,000	110	1.32	B	②
FBD7530B12W5-81	★	12	6.0~13.8	8.70	5.60	23.60	2,500	150	1.80	B	③
FBD7530B12W7-81	★	12	6.0~13.8	10.00	10.30	38.90	3,000	230	2.76	B	④
FBD7530B12W9-81	★	12	6.0~13.8	12.40	12.50	43.30	3,500	280	3.36	B	⑤
FBD7530B12W11-81	★	12	6.0~13.8	14.40	18.10	45.80	4,000	510	6.12	B	⑥
FBD7530B24W9-81	★	24	12.0~27.6	12.40	12.50	43.30	3,500	230	5.52	B	⑤

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

