

DC BLOWER 180x171x81mm



Housing: Thermoplastic PBT, UL 94V-0 and Aluminum Alloy.
Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
Lead Wire: UL Type #22 AWG
Weight: 926 g **Packing:** 12PCS/CTN



SS

IP

SF

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD1881B24W3-61	★▲ 24	12.0~27.6	138.90	64.80	62.10	2,000	2200	52.80	B	①
FBD1881B48W3-61	★▲ 48	24.0~55.2	138.90	64.80	62.10	2,000	1100	52.80	B	①

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

