

DC AXIAL FAN 40x40x07mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 11 g Packing: 400PCS/CTN



DC Axial Fans

| Model Number | Voltage (VDC) | Op.Voltage (VDC) | Air Flow (CFM) | Static Pres. (mm-H ₂ O) | Noise (dBA) | Speed (RPM) | Current (mA) | Power (W) | Available Bearing | Curves |
|----------------|---------------|------------------|----------------|------------------------------------|-------------|-------------|--------------|-----------|-------------------|--------|
| FD4007B05W5-71 | 5 | 4.0~5.5 | 5.50 | 2.50 | 29.50 | 6,500 | 230 | 1.15 | B,S | ① |
| FD4007B05W7-71 | 5 | 4.0~5.5 | 6.60 | 3.30 | 33.30 | 7,500 | 250 | 1.25 | B,S | ② |
| FD4007B12W5-71 | 12 | 10.8-13.2 | 5.50 | 2.50 | 29.50 | 6,500 | 110 | 1.32 | B,S | ① |
| FD4007B12W7-71 | 12 | 10.8-13.2 | 6.60 | 3.30 | 33.30 | 7,500 | 130 | 1.56 | B,S | ② |

• For "Sleeve" bearing version, change the "B" in the model number to "S".

Specifications are subject to change without notice

