

AC AXIAL FAN 172x150x51mm



Housing: Die-Cast Aluminum, Painted Black

Blade: Thermoplastic PBT, UL 94V-0

Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame

Dielectric Strength: 1500VAC for one minute

Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)

Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)

Motor Protection: Thermal Protected

Weight: 970 g **Packing:** 16PCS/CTN



SS

Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1751B11T7C-31 ※	115	50/60	253.8/297.4	16.2/20.3	55.2/60.1	2,850/3,300	350/400	46/50	B	①/②
FA1751B22T7C-31	230	50/60	253.8/297.4	16.2/20.3	55.2/60.1	2,850/3,300	200/220	46/50	B	①/②

- For "Wire Lead" version, change the "T" in the model number to "W".
- If model depicts "※", TUV approvals can be implemented upon request.

Specifications are subject to change without notice

