

AC AXIAL FAN Ø 170x51mm



Housing: Die-Cast Aluminum, Painted Black
Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 100MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minute
Operation Temperature: -20°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)
Motor Protection: Thermal Protected
Weight: 875 g **Packing:** 20PCS/CTN

Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1751B11T5C-51	115	50/60	100.0/121.0	4.6/6.4	39.0/44.0	1,450/1,750	150/150	17/16	B	①/②
FA1751B11T7C-51	115	50/60	195.0/225.0	15.5/16.8	57.0/61.0	2,900/3,300	220/280	25/31	B	③/④
FA1751B22T5C-51	230	50/60	101.0/120.0	4.6/6.4	39.0/44.0	1,450/1,750	60/60	14/13	B	①/②
FA1751B22T7C-51	230	50/60	195.0/225.0	15.5/16.8	57.0/61.0	2,900/3,300	110/140	24/30	B	③/④

• For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

