

DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 15%-65%RH)
 Storage Temperature: -20°C~85°C(Humidity 15%-65%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 51.6 g Packing: 200PCS/CTN



- High Airflow
- Extremely High Static Pressure

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W3-88	★▲	12	6.0~13.8	19.20	21.80	3,000	120	1.44	B,S	①
FD6025B12W5-88	★▲	12	6.0~13.8	23.20	25.70	3,600	150	1.80	B,S	②
FD6025B12W7-88	★▲	12	6.0~13.8	27.40	29.90	4,200	170	2.04	B,S	③
FD6025B12W9-88	★▲	12	6.0~13.8	33.80	35.00	5,000	220	2.64	B,S	④
FD6025B24W3-88	★▲※	24	12.0~26.0	19.20	21.80	3,000	120	2.88	B,S	①
FD6025B24W5-88	★▲※	24	12.0~26.0	23.20	25.70	3,600	150	3.60	B,S	②
FD6025B24W7-88	★▲※	24	12.0~26.0	27.40	29.90	4,200	170	4.08	B,S	③
FD6025B24W9-88	★▲※	24	12.0~26.0	33.80	35.00	5,000	220	5.28	B,S	④

- If model depicts "★", auto restart protection built in.
- If model depicts "▲", polarity protection function built in.
- If model depicts "※", UL approvals can be implemented upon request.

Specifications are subject to change without notice

