


Standard Pluggable PCB Terminal Block Header

The CPM family of printed circuit board headers is used with the CPF and MRT3 pluggable terminal blocks. The CPM is available in both a vertical and 90 degree version and with either open or closed ends. A feature of the CPM header is the molded-in polarization that insures proper mating of the plug. The CPM headers are available in 2 to 24 positions and have a UL rating of 12 amps, 300 volts. The standard color is green, however other colors are available upon request.

SPECIFICATIONS

Housing Material: PA68 Polyamide, Flammable UL94V0
 Housing Color: Green
 Screw: Zinc Plated Steel
 Clamp: Nickel Plated Brass
 Pin: Tin Plated Brass
 P.C.B. mounting hole: 1.6mm
 Nominal current: 12 A
 Voltage: 300 V
 Temperature Range: -30° C to 85° C



CPM .../...		CPM .../...SQ		Catalog #	No. of Positions	Length (mm)
P	L mm			CPM5.08-2SQA	2	10.16
5	5 x p +1.2			CPM5.08-3SQA	3	15.24
5.08	5.08 x p +1.2			CPM5.08-4SQA	4	20.32
10	10 x p -3.8			CPM5.08-5SQA	5	25.40
10.16	10.16 x p -3.88			CPM5.08-6SQA	6	30.48
				CPM5.08-7SQA	7	35.56
				CPM5.08-8SQA	8	40.64
				CPM5.08-9SQA	9	45.72
				CPM5.08-10SQA	10	50.80
				CPM5.08-11SQA	11	55.88
				CPM5.08-12SQA	12	60.96
				CPM5.08-13SQA	13	66.04
				CPM5.08-14SQA	14	71.12
				CPM5.08-15SQA	15	76.20
				CPM5.08-16SQA	16	81.28
				CPM5.08-17SQA	17	86.36
				CPM5.08-18SQA	18	91.44
				CPM5.08-19SQA	19	96.52
				CPM5.08-20SQA	20	101.60
				CPM5.08-21SQA	21	106.68
				CPM5.08-22SQA	22	111.76
				CPM5.08-23SQA	23	116.84
				CPM5.08-24SQA	24	121.92

To locate additional product specifications and technical drawings go to www.asi-ez.com