



<b>Anode Cathode</b>	common anode
<b>Chip Type</b>	G
<b>LED Type</b>	
<b>Display housing</b>	19,05mm x 12,70mm
<b>Display Kind</b>	Standard
<b>Display Size</b>	14,22mm
<b>Emitted color</b>	Green
<b>Lens color</b>	White
<b>Surface color</b>	Gray
<b>Lum in min (mcd)</b>	1.900mcd
<b>Lum in type (mcd)</b>	10.500mcd
<b>Reverse voltage</b>	5V
<b>Forward current</b>	25mA
<b>Peak forward current</b>	140mA*
<b>Power Dissipation</b>	105mW
<b>Op. temperature (°C)</b>	-40°C to +85°C
<b>Storage temperature (°C)</b>	-40°C to +85°C
<b>Forward volt typ.</b>	2,2V
<b>Forward volt max.</b>	2,5V
<b>Dom wave length</b>	568nm
<b>Peak Wave Lenght (mA)</b>	565nm
<b>Spectral half width</b>	30nm
<b>Comments</b>	* 1/10 Duty Circle, 0,1ms Pulse Width

Drawn : DIL	Ch'd : DIL	Datasheet : SA5611	Print date : 29/04/06
Revision :	Revision date : 2006-03-02	Name : DIL	Scale :