



<b>Anode Cathode</b>	common cathode
<b>Chip Type</b>	PB
<b>LED Type</b>	
<b>Display housing</b>	17,78mm x 12,70mm
<b>Display Kind</b>	Dot Matrix
<b>Display Size</b>	2,00mm
<b>Emitted color</b>	Blue
<b>Lens color</b>	White
<b>Surface color</b>	Gray
<b>Lum in min (mcd)</b>	4.700mcd
<b>Lum in type (mcd)</b>	13.200mcd
<b>Reverse voltage</b>	5V
<b>Forward current</b>	30mA
<b>Peak forward current</b>	160mA*
<b>Power Dissipation</b>	102mW
<b>Op. temperature (°C)</b>	-40°C to +85°C
<b>Storage temperature (°C)</b>	-40°C to +85°C
<b>Forward volt typ.</b>	3,65V
<b>Forward volt max.</b>	4,2V
<b>Dom wave length</b>	470nm
<b>Peak Wave Lenght (mA)</b>	468nm
<b>Spectral half width</b>	25nm
<b>Comments</b>	* 1/10 Duty Circle, 0,1ms Pulse Width

Drawn : DIL	Ch'd : DIL	Datasheet : TC0711	Print date : 29/04/06
Revision :	Revision date : 2006-03-02	Name : DIL	Scale :