




CROSS FITTING




CATALOG NUMBER	DIMENSIONS			DESCRIPTION
	A	B	G	
1150 CR2065	2.000	2.000	10.000	Regular
1150 CR4065	4.000	4.000	14.000	Regular
1150 CR4665	6.000	4.000	16.000	Regular
1150 CR6065	6.000	6.000	16.000	Regular
1150 CR2065P	2.000	2.000	10.000	Perforated
1150 CR4065P	4.000	4.000	14.000	Perforated
1150 CR4665P	6.000	4.000	16.000	Perforated
1150 CR6065P	6.000	6.000	16.000	Perforated



OFFSET TO THE LEFT



CATALOG NUMBER	DIMENSIONS				DESCRIPTION
	A	B	C	D	
1150 OS20325	2.000	2.000			Regular
1150 OS40325	4.000	4.000			Regular
1150 OS46325	6.000	4.000			Regular
1150 OS60325	6.000	6.000			Regular
1150 OS20325P	2.000	2.000			Perforated
1150 OS40325P	4.000	4.000			Perforated
1150 OS46325P	6.000	4.000			Perforated
1150 OS60325P	6.000	6.000			Perforated
1150 OS20325Q	2.000	2.000			Quick Install
1150 OS40325Q	4.000	4.000			Quick Install
1150 OS46325Q	6.000	4.000			Quick Install
1150 OS60325Q	6.000	6.000			Quick Install
1150 OS20325QP	2.000	2.000			Quick/Perfor.
1150 OS40325QP	4.000	4.000			Quick/Perfor.
1150 OS46325QP	6.000	4.000			Quick/Perfor.
1150 OS60325QP	6.000	6.000			Quick/Perfor.



OFFSET TO THE RIGHT

CATALOG NUMBER	DIMENSIONS				DESCRIPTION
	A	B	C	D	
1150 OS20326	2.000	2.000			Regular
1150 OS40326	4.000	4.000			Regular
1150 OS46326	6.000	4.000			Regular
1150 OS60326	6.000	6.000			Regular
1150 OS20326P	2.000	2.000			Perforated
1150 OS40326P	4.000	4.000			Perforated
1150 OS46326P	6.000	4.000			Perforated
1150 OS60326P	6.000	6.000			Perforated
1150 OS20326Q	2.000	2.000			Quick Install
1150 OS40326Q	4.000	4.000			Quick Install
1150 OS46326Q	6.000	4.000			Quick Install
1150 OS60326Q	6.000	6.000			Quick Install
1150 OS20326QP	2.000	2.000			Quick/Perfor.
1150 OS40326QP	4.000	4.000			Quick/Perfor.
1150 OS46326QP	6.000	4.000			Quick/Perfor.
1150 OS60326QP	6.000	6.000			Quick/Perfor.

