


STRAIGHT SECTION


CATALOG NUMBER	DIMENSIONS		DESCRIPTION
	A	B	
1150 SS20120	2.000	2.000	Regular
1150 SS40120	4.000	4.000	Regular
1150 SS46120	6.000	4.000	Regular
1150 SS60120	6.000	6.000	Regular
1150 SS20120P	2.000	2.000	Perforated
1150 SS40120P	4.000	4.000	Perforated
1150 SS46120P	6.000	4.000	Perforated
1150 SS60120P	6.000	6.000	Perforated



SCREW-ON BARRIER

Subdivides a straight section in two.


CATALOG NUMBER	DIMENSIONS		DESCRIPTION
	A	B	
1150 BA40120	—	4.000	Regular
1150 BA60120	—	6.000	Regular



TELESCOPE FITTING


Sets between 16.000 in. and 28.000 in.

CATALOG NUMBER	DIMENSIONS			DESCRIPTION
	A	B	C	
1150 TL2068	2.000	2.000	—	Regular
1150 TL4068	4.000	4.000	—	Regular
1150 TL4668	6.000	4.000	—	Regular
1150 TL6068	6.000	6.000	—	Regular



STRAIGHT SECTION CONNECTOR

CATALOG NUMBER	DIMENSIONS		DESCRIPTION
	A	B	
1150 SSC20	2.000	2.000	Regular
1150 SSC40	4.000	4.000	Regular
1150 SSC46	6.000	4.000	Regular
1150 SSC60	6.000	6.000	Regular
1150 SSC20P	2.000	2.000	Perforated
1150 SSC40P	4.000	4.000	Perforated
1150 SSC46P	6.000	4.000	Perforated
1150 SSC60P	6.000	6.000	Perforated



DIVIDER FOR STRAIGHT SECTION CONNECTOR

CATALOG NUMBER	DIMENSIONS		DESCRIPTION
	A	B	
1150 SSC40 - DIV	—	4.000	Regular
1150 SSC60 - DIV	—	6.000	Regular

