1412 X NEMA 4-4X PULL THROUGH WIREWAY

STAINLESS STEEL WATERTIGHT PULL THROUGH WIREWAY


The 1412 X series is a complete water tight wireway system, which is used indoor or outdoors, in areas where corrosion may be a problem, or where the wireway may be subjected to hosing or water coming from any direction.

CSA Certified / UL Listed
NEMA/EEMAC 4X / IP66


Technical specifications:

- Troughs are bolt-on and are made of high quality code gauge (Type 304) stainless steel, with welded end flanges.
- All seams have been continuously welded.
- Covers are hinged and secure closing is assured by several, quick-release, ¼ turn locks.
- A high quality, poured-in-place, seamless gasket is installed between the door and trough, and between the sections and accessories to ensure integrity.
- The enclosures exterior is unpainted and brushed smooth.


DESCRIPTION	CATALOG NUMBER			
	2½ X 2½ po	4 X 4 po	6 X 6 po	8 X 8 po
Straight sections 6"	1412 XSS2006	1412 XSS4006	1412 XSS6006	1412 XSS8006
Straight sections 12"	1412 XSS2012	1412 XSS4012	1412 XSS6012	1412 XSS8012
Straight sections 24"	1412 XSS2024	1412 XSS4024	1412 XSS6024	1412 XSS8024
Straight sections 36"	1412 XSS2036	1412 XSS4036	1412 XSS6036	1412 XSS8036
Straight sections 48"	1412 XSS2048	1412 XSS4048	1412 XSS6048	1412 XSS8048
Straight sections 60"	1412 XSS2060	1412 XSS4060	1412 XSS6060	1412 XSS8060
Straight sections 120"	1412 XSS2120	1412 XSS4120	1412 XSS6120	1412 XSS8120
Screw on barrier 60"	--	1412 BA4060	1412 BA6060	1412 BA8060
Cut off fitting	1412 XCO4062	1412 XCO6062	1412 XCO8062	
Nipple 1"	1412 XNS2001	1412 XNS4001	1412 XNS6001	1412 XNS8001
Nipple 2"	1412 XNS2002	1412 XNS4002	1412 XNS6002	1412 XNS8002
Nipple 3"	1412 XNS2003	1412 XNS4003	1412 XNS6003	1412 XNS8003
Swivel nipple	1412 XSN2002	1412 XSN4002	1412 XSN6002	1412 XSN8002
Flexible fitting	1412 XFF2003	1412 XFF4003	1412 XFF6003	1412 XFF8003
Telescope fitting	1412 XTL2068	1412 XTL4068	1412 XTL6068	1412 XTL8068
Elbow 90°	1412 XEL2090	1412 XEL4090	1412 XEL6090	1412 XEL8090
Elbow 45°	1412 XEL2045	1412 XEL4045	1412 XEL6045	1412 XEL8045
Elbow 22½°	1412 XEL2022	1412 XEL4022	1412 XEL6022	1412 XEL8022
Tee fitting	1412 XTT2063	1412 XTT4063	1412 XTT6063	1412 XTT8063
Cross fitting	1412 XCF2065	1412 XCF4065	1412 XCF6065	1412 XCF8065
Center reducer 4X4 to 2½X2½"	--	1412 XRDC4402	--	--
Center reducer 6X6 to 4X4"	--	--	1412 XRDC6604	--
Center reducer 8X8 to 6X6"	--	--	--	1412 XRDC8806
Edge reducer 4X4 to 2½X2½"	--	1412 XRDE4402	--	--
Edge reducer 6X6 to 4X4"	--	--	1412 XRDE6604	--
Edge reducer 8X8 to 6X6"	--	--	--	1412 XRDE8806
Drop hanger	1412 XDH2068	1412 XDH4068	1412 XDH6068	1412 XDH8068
Bracket hanger	1412 XBH2069	1412 XBH4069	1412 XBH6069	1412 XBH8069
Closing plate	1412 XCP2070	1412 XCP4070	1412 XCP6070	1412 XCP8070
Box connector	1412 XBC2067	1412 XBC4067	1412 XBC6067	1412 XBC8067




BARRIERS



STRAIGHT SECTIONS



CUT OFF FITTINGS



TELESCOPE FITTINGS


CATALOG NUMBER	DIMENSIONS Z
1412 XBA4060	3.000
1412 XBA6060	4.500
1412 XBA8060	6.000








DATA SUBJECT TO CHANGE WITHOUT NOTICE.




ELBOW 90°

CATALOG NUMBER	DIMENSIONS A	B	G
1412 XEL2090	2.500	2.500	4.250
1412 XEL4090	4.000	4.000	5.000
1412 XEL6090	6.000	6.000	6.000
1412 XEL8090	8.000	8.000	7.000

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Welded flanges
- Seamless welding
- Stainless steel






ELBOW 45°

CATALOG NUMBER	DIMENSIONS A	B	H
1412 XEL2045	2.500	2.500	2.000
1412 XEL4045	4.000	4.000	2.437
1412 XEL6045	6.000	6.000	3.000
1412 XEL8045	8.000	8.000	3.750

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Welded flanges
- Seamless welding
- Stainless steel






ELBOW 22½°

CATALOG NUMBER	DIMENSIONS A	B
1412 XEL2022	2.500	2.500
1412 XEL4022	4.000	4.000
1412 XEL6022	6.000	6.000
1412 XEL8022	8.000	8.000

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Welded flanges
- Seamless welding
- Stainless steel






TEE FITTING

CATALOG NUMBER	DIMENSIONS A	B	F	I
1412 XTT2063	2.500	2.500	8.500	4.250
1412 XTT4063	4.000	4.000	10.000	5.000
1412 XTT6063	6.000	6.000	12.000	6.000
1412 XTT8063	8.000	8.000	14.000	7.000

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Welded flanges
- Seamless welding
- Stainless steel






CROSS FITTING

CATALOG NUMBER	DIMENSIONS A	B	F
1412 XCF2065	2.500	2.500	8.500
1412 XCF4065	4.000	4.000	10.000
1412 XCF6065	6.000	6.000	12.000
1412 XCF8065	8.000	8.000	14.000

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Welded flanges
- Seamless welding
- Stainless steel





REDUCER - CENTER HOLE

CATALOG NUMBER	DIMENSIONS A	B	D	E
1412 XRDC4402	2.500	2.500	4.000	4.000
1412 XRDC6604	4.000	4.000	6.000	6.000
1412 XRDC8806	6.000	6.000	8.000	8.000

Features :
- Joining gasket
- Carriage bolts
- Anti-vibration hardware
- Reducer with edge hole is also available, see model 1412 XRDE.

