

ARCA ARK14126CHFSSL



Order symbol: ARK14126CHFSSL EAN: 6418074097460

Product nbr:8561570El. number:Description:PC EnclosureFinland:

Remarks: Hinged opaque flat cover w/S.S. Lockable latch. Base includes

1/2 and 3/4 inch knock-outs

Including: Hinged cover. Base with 10-32 brass inserts, latched flat cover with formed in place PUR gasket, stainless hinge pin. Base with 1/2 and 3/4 inch knock-outs. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Sample photo

Dimensions:	Length	Width	Height
mm:	305	254	127
inch:	12.0	10.0	5.0

Materials

Material:PolycarbonateBase colour:RAL 7035 -light greyCover screws material:Stainless steelCover colour:RAL 7035 -light greyGasket material:Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 140 °C

Temperature °C (continuous): -40 ... 80 °C

Temperature °F (short term): -40 ... 284 °F

Temperature °F (continuous): -40 ... 175 °F

Accessories:

ABP1412 Painted Steel Back Panel

Accessories:	
ALBP1412	Aluminum Back Panel
ADFP1412	Dead Front Panel w/ screws
ASP1412	Aluminum Swing Panel
ASPK1412	Swing Panel Kit incl. Panel
ASPHK14	Swing Panel Kit w/o Panel
AMFL12	12" Mounting Flange Set

Rating

Ingress Protection (EN 60529): IP66/IP67 Impact Resistance (EN 62262): IK09 Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): 1

UV resistance: UL 508 Flammability Rating: UL 508 Glow Wire Test (IEC 695-2-1) °C: 960

NEMA Class: NEMA 4, 4X, 12 and 13

Certificates:

Gost R

