

## ARCA ARK14126FSC



<b>Order symbol:</b>	ARK14126FSC
<b>Product nbr:</b>	8561577
<b>Description:</b>	PC Enclosure
<b>Remarks:</b>	Opaque flat scre cover, base includes 1/2 and 3/4 inch knock-outs.

**EAN:** 6418074097538  
**El. number:**  
Finland:

Including: Flat screw cover. Base with 10-32 brass inserts, cover with formed in place PUR gasket and 4 stainless cover screws. Base includes 1/2 and 3/4 inch knock outs. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting

Sample photo

Dimensions:			Accessories:	
mm:	Length	Width	Height	
mm:	305	254	127	ALBP1412 Aluminum Back Panel
inch:	12.0	10.0	5.0	ADFP1412 Dead Front Panel w/ screws
Materials:			ASP1412 Aluminum Swing Panel	
Material:	Polycarbonate		ASPK1412 Swing Panel Kit incl. Panel	
Base colour:	RAL 7035 -light grey		ASPHK14 Swing Panel Kit w/o Panel	
Cover screws material:	Stainless steel		AMFL12 12" Mounting Flange Set	
Cover colour:	RAL 7035 -light grey		Rating:	
Gasket material:	Polyurethane		Ingress Protection (EN 60529): IP66/IP67	
Temperatures:			Impact Resistance (EN 62262): IK09	
Temperature °C (short term):	-40 ... 140 °C		Electrical insulation: Totally insulated	
Temperature °C (continuous):	-40 ... 80 °C		Halogen free (DIN/VDE 0472, Part 815): 1	
Temperature °F (short term):	-40 ... 284 °F		UV resistance: UL 508	
Temperature °F (continuous):	-40 ... 175 °F		Flammability Rating: UL 508	
Accessories:			Glow Wire Test (IEC 695-2-1) °C: 960	
ABP1412	Painted Steel Back Panel		NEMA Class: NEMA 4, 4X, 12 and 13	
Accessories:			Certificates:	
			Gost R	

