



Product #: 5824039

Order Symbol: UL TPC 111107

Description: Enclosure, PC

Remarks: Grey Cover

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch | 4.3 | 4.3 | 2.6 |
| mm | 110 | 110 | 65 |

| Materials | |
|------------------|----------------------|
| Material: | Polycarbonate |
| Base color: | RAL 7035 -light grey |
| Cover color: | RAL 7035 -light grey |
| Gasket material: | Polyurethane |

| Temperatures | |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 140 |
| Temperature °C (continuous): | -40 ... 80 |

| Ratings | |
|--|------------------------------------|
| Impact Resistance (EN 62262): | IK07/IK08 |
| Electrical insulation: | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): | No |
| UV resistance: | UL 508 |
| Flammability Rating: | UL94-5VA (f1)/ Cover: UL94-V0 (f1) |
| Glow Wire Test (IEC 60695): | 960 °C |
| UL/cUL Type: | 1, 4, & 4X |