

Circuit Disconnect Terminal Blocks

The circuit disconnect terminal blocks provide a means of opening circuits without disturbing the wiring that is already in place. This feature is especially beneficial when inserting a measuring device such as a meter in series in the circuit. Several varieties of disconnect terminal blocks are available, including knife disconnect in both screw clamp and spring clamp terminations. Sliding link versions, which are popular in the utility industry, are also available as shown.



Terminal width .24" (6.2mm)

Wire strip length .47" (12mm)



Terminal width .31" (8mm)

Wire strip length .47" (12mm)

SCB.4

SCB.6

Specifications			WIRE RANGE	CURRENT (A)	VOLTAGE (V)	WIRE RANGE	CURRENT (A)	VOLTAGE (V)
Connection Data 1059 No. 22-2, No. 150 IEC 947-7-1	8		20 - 12 AWG 20 - 12 AWG 20 - 12 AWG 0.5 - 4mm	20 25 24	600 300 800	20 - 8 AWG 20 - 8 AWG — 0.5 - 6mm	47 41	600 800
ORDERING INFORMAT	TION		Түре	CATALOG NO.	Pcs/Pkg	Түре	CATALOG NO.	Pcs/Pkg
wit	block, andard th bridge x)i version	Beige Beige Blue	SCB.4	SB100	75	SCB.6	SB200	100
Accessories			ТүрЕ	CATALOG NO.	Pcs/Pkg	Түре	CATALOG NO.	Pcs/Pkg
End cover, width .06"	" (1.5mm)	Beige Blue	SCB/4/PT	SB101	25	SCB/6/PT	SB201	25
Circuit bridges, pre-assembled internal bridge 2 position 3 position 5 position 10 position			PM41/2 PM41/3 PM41/5 PM41/10	PM412 PM413 PM415 PM410	25 25 25 10	_ _ _ _		
External bridge,			_			POF/57	POF57	25
Multiple circuit bridge bar, (250mm) 2 through 45 circuits based on length, used with bridge kit, CPM			PMP/02	PMP02	8	PMP/13	PMP13	8
Circuit bridge kit, consisting of screw and spacer, used with bridge bar			CPM/01	CPM01	25	CPM/57	CPM57	25
Partition plate,	R	Vhite Red Green	DFU/3/B DFU/3/R DFU/3/V	DU03B DU03R DU03V	50 50 50	DFU/6/B DFU/6/R DFU/6/V	DU06B DU06R DU06V	25 25 25
Test socket, for circuit testing with test plug (SDD)			PSD/A	PD001	50	PSD/P	PD015	50
Test plug, for circuit testing with test socket (PSD)			SDD/1	DD001	50	SDD/2	DD002	50
Marking system,	blank mar printed ma custom m universal	arker arker	SNZ/60/00 SNZ/60/ CM CNU/8/030	SN007 SN7 CM NU008	60 60 5	SNZ/8/00 SNZ/8/ CM CNU/8/030	SN004 SN4 CM NU008	60 60 5
End stop, width .31" (8	8mm) universal 35mm rail	only	BTU BT/3	BT005 BT003	25 25	BTU BT/3	BT005 BT003	25 25
Mounting rail, DIN (2 meter length) non-slotted symmetrical 35mm x 7.5mm slotted symmetrical 35mm x 7.5mm non-slotted symmetrical 35mm x 15mm slotted symmetrical 35mm x 15mm			PR/3/AC PR/3/AS PR/3/PP PR/3/PA	PR003 PR005 PR007 PR006	1 1 1 1	PR/3/AC PR/3/AS PR/3/PP PR/3/PA	PR003 PR005 PR007 PR006	1 1 1 1