# **PLASTICASE**


STYLES A & B

### **DESIGN FEATURES**

- Impact resistant polystyrene
- · UL94-HB flammability rating
- · Molded-in card guides and mounting bosses
- · Comes complete with plated steel screws & rubber feet
- Finish Double-Textured PC Bone Gray
- · Shipped assembled

Catalog		Exterr	ıal Dimei	nsions	Intern	al Dimen	sions*	Panel	Weight
Number	Style	Α	В	C	D	Ε	F	Size	Oz.
PC-11402	Α	1.53"	5.08"	5.30"	1.28"	4.78"	4.78"	1.31"×4.75"×.06"	6
PC-11403	Α	1.53″	7.06"	5.30″	1.28″	6.76″	4.78″	1.31"×6.73"×.06"	8
PC-11404	Α	1.55"	6.33"	9.62"	1.30″	6.03″	9.03″	1.33"×5.99"×.09"	12
PC-11406	Α	2.52"	6.12"	6.32"	2.27"	5.77"	5.73"	2.31"×5.75"×.09"	11
PC-11408	Α	2.52"	8.10"	6.32"	2.27"	7.75″	5.73″	2.31"×7.75"×.09"	12.5
PC-11410	В	3.30"	6.12"	6.32"	3.05″	5.77″	5.73″	3.09"×5.75"×.09"	12
PC-11412	В	3.30"	8.10"	6.32"	3.05"	7.75″	5.73"	3.09"×7.75"×.09"	14
PC-11414	В	4.04"	6.12"	6.32"	3.79"	5.77"	5.73″	3.83"×5.75"×.09"	14.5
PC-11416	В	4.04"	8.10"	6.32″	3.79"	7.75″	5.73″	3.83"×7.75"×.09"	15.5
PC-11418	В	2.06"	5.08"	5.30″	1.81″	4.78″	4.78″	1.84"×4.75"×.06"	7
PC-11420	В	2.06"	7.06"	5.30″	1.81″	6.76″	4.78"	1.84"×6.73"×.06"	9
	*Refer	ence only	- Reques	t drawing	for interr	nal configu	uration an	d dimensions.	

These sturdy enclosures come in a variety of styles and sizes and are constructed of high quality plastic materials. Housing designs allow complete accessibility to internal components. Contact Bud factory for optional colors, materials, EMI/RFI shielding, and custom modifications.



# **STYLE C**

#### **DESIGN FEATURES**

- · Black ABS covers, UL94-HB flammability rating
- · Clear anodized aluminum front and rear panels
- · Internal steel channels provide extra strength and ease of assembly
- Formed guide tabs accept vertical or horizontal circuit boards
- · Shipped assembled
- PC-11432 -no foot supplied. PC-11438 folding plastic feet supplied

Catalog	Exteri	nal Dimer	isions	Intern	al Dimen	sions*	Panel	Weight Oz.		
Number	Α	В	C	D	E	F	Size			
PC-11432	1.61″	3.54"	5.71″	1.42"	3.21"	5.12"	1.42"×3.28"×.04"	7		
PC-11438	4.02"	9.72"	8.66"	3.74"	9.27"	8.07"	3.83"×9.46"×.04"	22		
*Reference only - Request drawing for internal configuration and dimensions.										






## STYLE D

# **DESIGN FEATURES**

- · Molded in card guides and mounting bosses
- Available in four versions:
  - #1 Dark gray ABS covers with light gray ABS end panels. UL94V-0 flammability rating.
  - #2 Dark gray ABS covers with natural finish aluminum end panels. UL94V-0 flammability rating.
  - #3 Light gray ABS covers with black ABS end panels UL94-HB flammability rating.
  - #4 Light gray ABS covers with natural finish aluminum end panels. UL94-HB flammability rating.

	Catal	External Dimensions			Intern	al Dimen:	sions*		Weight		
Version 1	Version 2	Version 3	Version 4	Α	В	C	D	E	F	Panel Size	Oz.
PC-11480	PC-11480-A	PC-11480-LG	PC-11480-LGA	1.38″	5.51″	4.33"	1.18″	5.32"	4.07"	1.20"×5.31"×.07"	4.6
PC-11481	PC-11481-A	PC-11481-LG	PC-11481-LGA	1.57"	8.86″	6.50"	1.35"	8.62"	6.24"	1.37"×8.62"×.07"	12.3
PC-11482	PC-11482-A	PC-11482-LG	PC-11482-LGA	2.56"	10.24″	7.09"	2.32"	10.00″	6.78"	2.36"×10.00"×.07"	17.8
	*Reference only - Request drawing for internal configuration and dimensions										







# **PLASTICASE**

## **STYLE E**

#### **DESIGN FEATURES**

- Light gray ABS covers with dark gray ABS end panels. UL94-HB flammability rating
- Internal PCB mounting bosses and card guides
- Includes rubber feet







Catalog	Exter	nal Dime	ensions	Intern	al Dimen	sions*	Panel	Weight
Number	Α	В	C	D	E	F	Size	Oz.
PC-11460	1.42"	3.74"	6.22"	1.18″	3.50"	5.81″	1.20"×3.48"×.09"	5.2
PC-11461	1.85″	3.74"	6.22"	1.61″	3.50"	5.81″	1.63"×3.48"×.09"	5.7
PC-11462	2.28"	3.74"	6.22"	2.09"	3.50"	5.81″	2.07"×3.48"×.09"	6.3
PC-11463	1.42″	6.14"	7.09"	1.14"	5.86″	6.68″	1.20"×5.86"×.09"	9.0
PC-11464	1.73″	6.14"	7.09"	1.45"	5.86″	6.68″	1.52"×5.86"×.09"	9.6
PC-11465	2.05"	6.14"	7.09"	1.77″	5.86″	6.68″	1.83"×5.86"×.09"	10.2
PC-11466	1.57"	5.51"	7.48"	1.34"	5.19"	7.07″	1.36"×5.15"×.09"	8.9
PC-11467	2.40"	5.51″	7.48"	2.12"	5.19"	7.07″	2.14"×5.15"×.09"	10.0
PC-11468	3.15″	5.51″	7.48"	2.91″	5.19"	7.07″	2.93"×5.15"×.09"	11.2
PC-11469	1.57″	7.87"	11.02"	1.34″	7.63"	10.61″	1.36"×7.59"×.09"	16.2
PC-11470	2.40"	7.87"	11.02"	2.12"	7.63"	10.61″	2.14"×7.59"×.09"	18.3
PC-11471	3.15″	7.87"	11.02"	2.91"	7.63"	10.61″	2.93"×7.59"×.09"	20.4
	*Refere	nce only	- Request o	drawing for	r internal c	onfiguratio	n and dimensions.	

# **STYLE F** Molded in PCB mounting bosses. Three versions.

- Version #1: Light gray ABS covers with rear mounted dark gray ABS cable access panel and natural finish aluminum sloped panel. UL94-HB flammability rating.
- Version #2: Light gray ABS covers with horizontal insert area in top cover, rear mounted dark gray ABS cable access panel, and natural finish aluminum sloped panel. UL94-HB flammability rating.
- Version #3: Light gray ABS covers with vertical panel space in top cover, rear mounted dark gray ABS cable access panel, and natural finish aluminum panels in both vertical and sloped areas. UL94-HB flammability rating.








# **STYLE G**

This is a four-piece box including the base, cover, and two end panels. Unique, contemporary styling with rounded corners and edges. Durable, self-extinguishing, ABS plastic material with UL94-5VA flammability rating. Mar-resistant textured surface. Internal PCB mounting bosses. Base is securely attached to the cover with four color matched screws. **Standard color:** Black



Catalog		Exte	rnal			Wt.			
Number	Α	В	C	D	E	F	G	Oz.	
PC-11535	5.00"	3.80"	1.50″	.55″	4.73"	3.60"	1.29"	4.2	
PC-11555	5.50″	5.25″	1.63″	.55″	5.23"	5.05"	1.41″	6.2	
PC-11565	6.75″	6.25″	1.63″	.55″	6.49″	6.06"	1.41″	8.9	
*Reference only - Request drawing for internal configuration and dimensions.									

For full dimensional information, see our Web site at www.budind.com.

## STYLE H

This contemporary styled enclosure features a unique interlocking design that allows it to be stacked several high without slipping. Removable front and rear panels accommodate easy modification, and internal bosses allow for PCB



mounting. Enclosure is made of ABS plastic in black finish with a UL94V-0 flammability rating.

Catalog		Exte	rnal			Wt.		
Number	Α	В	C	D	Е	F	G	Oz.
PC-11640	9.18"	5.25"	1.68"	.88″	8.81"	5.40"	1.20"	8.7
PC-11645	9.18″	5.25″	2.36″	.88″	8.81"	5.40"	1.88″	10.5

# STYLE I

Enclosure features unique, contemporary styling with rounded edges. Time-saving snaptogether four-piece design includes internal PCB mounting bosses on lid. Base and lid have textured surface, and recessed area in end panels has textured surface. ABS plastic material has UL94-HB flammability rating. Standard colors are light gray base and lid, gray end panels.



Catalog		Exte	rnal	Internal			
Number	Α	В	C	D	E	F	G
PC-11475	4.13"	1.61″	1.00"	.50″	4.00"	1.48"	0.85"
PC-11476	5.12"	3.00″	1.18″	.59″	4.96"	2.83"	1.02"
PC-11477	6.10″	3.62"	1.16″	.58″	5.90″	3.42"	0.94"
PC-11478	7.87"	4.76"	1.57″	.79″	7.64"	4.52"	1.34″

# **PLASTICASE**



### STYLE M

Sleek, rounded styling gives contemporary look to desktop, benchtop, and control-box devices. Optional external mounting flanges in base allow for wall- or equipment-mounting. Durable ABS plastic offers UL94-HB flammability rating. Has mar-resistant textured surface and optional internal PCB mounting bosses. Cover attaches to base with four screws.

	Base Base		External Base Mounting	Ex	cternal D	imensior	Internal Dimensions				
	Catalog No.	Bosses	Flanges	Α	В	C	D	E	F	G	
	PT-11850-PMB	Yes	No	3.08"	2.08"	1.00"	.07"	2.93"	1.93"	.85"	
	PT-11850-PXX	No	No	3.08"	2.08"	1.00″	.07"	2.93"	1.93"	.85″	
_	PT-11851-PMB	Yes	No	3.08"	2.08"	1.59″	.58″	2.93"	1.93″	1.45″	
_	PT-11851-FMB	Yes	Yes	3.08"	2.08"	1.59″	.58″	2.93"	1.93″	1.45″	
	PT-11852-PMB	Yes	No	4.11"	2.23"	1.00″	.07"	3.96"	2.07"	.84″	
	PT-11852-PXX	No	No	4.11"	2.23"	1.00"	.07"	3.96″	2.07"	.84″	
	PT-11853-PMB	Yes	No	4.11"	2.23"	1.59″	.58″	3.96″	2.07"	1.45″	
	PT-11853-FMB	Yes	Yes	4.11"	2.23"	1.59″	.58″	3.96″	2.07"	1.45″	

PLASTIC BOXES

# PI SERIES




The line of molded enclosures is ideally suited for instrumentation and telecommunications equipment from hand-held to desktop sizes. Available is twelve sizes and two versions.

Version #1 - Dark gray ABS covers with light gray ABS end panels. UL94V-0 flammability rating.

Version #2 - Light gray ABS covers with dark gray ABS end panels. UL94-HB flammability rating.

### **DESIGN FEATURES**

- Designed to IP 54 of IEC 529
- Two-part design with tongue and groove joint between top and bottom covers and specially designed end panels
- Internal guide slots provided for vertical mounting of PCBs
- Internal bosses provided for horizontal mounting of PCBs
- Top and bottom covers are lightly textured providing a scratch-resistant, high quality finish
- Four screws are countersunk in the bottom cover and thread into internal bosses, which secure the top cover and end panels



Catalog	Number	Exter	nal Dimen	sions	Intern	al Dimens	sions*		Weight
Version 1	Version 2	Α	В	C	D	E	F	Panel Size	Oz.
PI-1900	PI-1900-LG	.63″	1.97″	3.54"	.47″	1.64"	3.12"	.46" × 1.72" × .11"	1.7
PI-1901	PI-1901-LG	.94″	1.97″	3.54"	.78″	1.64″	3.12"	.77" × 1.72" × .11"	1.7
PI-1902	PI-1902-LG	1.26″	1.97″	3.54"	1.10″	1.64″	3.12"	1.09" × 1.72" × .11"	2.2
PI-1903	PI-1903-LG	1.18″	2.36″	4.72"	1.02″	1.99″	4.25"	.93" × 1.95" × .13"	2.7
PI-1904	PI-1904-LG	1.57″	2.36″	4.72"	1.41″	1.99″	4.25"	1.32" × 1.95" × .13"	3.2
PI-1905	PI-1905-LG	1.97″	2.36"	4.72"	1.81″	1.99"	4.25"	1.72" × 1.95" × .13"	4.0
PI-1906	PI-1906-LG	1.18″	3.15"	5.91"	1.02"	2.78"	5.46"	.93" × 2.74" × .13"	4.5
PI-1907	PI-1907-LG	1.77″	3.15″	5.91″	1.61″	2.78″	5.46"	1.52" × 2.74" × .13"	5.2
PI-1908	PI-1908-LG	2.36"	3.15″	5.91″	2.20″	2.78"	5.46"	2.11" × 1.66" × .13"	5.5
PI-1909	PI-1909-LG	1.57"	3.94″	7.48"	1.41″	3.48"	6.92"	1.29" × 3.45" × .13"	7.0
PI-1910	PI-1910-LG	2.36"	3.94″	7.48"	2.20"	3.48"	6.92"	2.06" × 3.45" × .13"	9.5
PI-1911	PI-1911-LG	3.15"	3.94″	7.48"	2.99"	3.48"	6.92"	2.86" × 3.45" × .13"	10.5
		*Reference	e only - Requ	uest drawing	for internal	configuratio	n and dime	nsions	