Snap-In Toggle Switches



Looking for an economical, easy to install toggle switch? Carling Technologies has the solution. The tried and true T-Series with bat style actuator. Installation is literally a snap for this veteran workhorse switch.

The T-Series with toggle actuator provides a cost effective alternative to expensive metal toggles. Snap-in installation is quick, easy and eliminates the need for cumbersome and costly mounting hardware. Simply snap the switch into a .550 X 1.125 rectangular hole and installation is complete.

This offering is ideal for usage in applications including Wet/Dry vacs, Appliances, Medical equipment, Audio/Visual, Lawn and Garden and sundry other markets.

Key Features/Benefits of the T-Series Snap-In Toggle:

- ON-OFF, ON-ON and ON-OFF-ON maintained circuitry
- Dielectric Strength: UL/CSA:1000V live to dead metal
- Electrical Life: 100,000 cycles
- Mechanical Life: 100,000 cycles
- Operating Temperature : 32°F to 185°F (0°C to 85°C)
- · Aesthetically appealing matte finish toggle and bezel
- One step snap-in mount for industry standard .550 X 1.125 mounting hole installs in seconds
- UL/CSA approved 10A 250 VAC, 15A 125VAC 3/4 HP 125-250VAC rating
- Durable, cost effective all nylon construction
- The performance and quality that you've come to expect from Carling Technologies

Product Bulletin #93 June 17, 2002

For additional information on our T-Series Snap-In Toggle Switches, please contact a Carling Technologies Technical Customer Service Rep:

Phone (860) 793-9281
Fax (860) 793-9231
email sales@carlingtech.com
mail Carling Technologies, Inc.
60 Johnson Avenue
Plainville, CT 06062-1177



T-Series Snap-In Toggle Switch Ordering Scheme

Base Part Number

TA201 - B R - B

1 BASE PART NUMBER: SERIES / CIRCUITRY / RATING / TERMINATION1

RATING 5 = 10A 250 VAC, 15A 125 VAC, 3/4 HP 125-250 VAC¹

.250 Tab

circuit⁴

 OFF-NONE-ON
 TA201

 ON-NONE-ON
 TB201

 ON-OFF-ON
 TC201

2 ACTUATOR STYLE

B Snap-In Toggle

3 ACTUATOR COLOR²

B BlackW WhiteR Red

4 BEZEL COLOR

B BlackW White

Color

Warranty Policy

Carling Technologies, Inc. (Seller) warrants that goods sold hereunder shall be free of defects in material and workmanship for one year from date of shipment.

In the event of such defects, the Seller's only obligation shall be the replacement or the cost of the defective goods, themselves, excluding, without limitation, labor costs, which are or may be required in connection with the replacement or reinstallation of the goods. This warranty is the Seller's sole obligation and excludes all other remedies or warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, whether or not purposes or specifications are described herein. This Warranty expressly excludes any and all incidental, special and/or consequential damages of any nature. Seller further disclaims any responsibility for injury to person or damage to or loss of property or value caused by any product which has been subjected to misuse, negligence, or accident; or misapplied, or modified or repaired by a person or persons not authorized by the Seller or which have been improperly installed.

NOTES

- 1 For additional rating requirements, consult factory.
- 2 Custom colors are available, consult factory.

