## **S8 Relay Series**

## Miniature high voltage relay






The coil pins are positioned near the centre of the relay while the contact pins are near the ends to give improved isolation between the High Voltage contacts and the low voltage coil.

- Space saving package
- Isolation Voltage across contacts 4kV or 5kV (dependent on coil voltage)
- Isolation Voltage 7kV contact to coil
- 2.5A carry current

Contact Specification		5V coil	12V coil	24V coil
Switch action			SPST (Form /	A)
Material			Rhodium	
Isolation across contact	s kV DC or AC peak	4	4	5
Switching Power Max.	VA		100	
Switching Voltage Max.	V		350dc/300ac	
Switching Current Max.	A DC or AC peak		1.0	
Carry Current Max A			2.5	
	F coil to screen		< 0.1	
contacts	grounded		0	
Lifetime operations	, .		10°	
	100W switching		107	
	nΩ max (typical)		80 (30)	
Insulation Resistance C	Omin (typical)		10 <sup>10</sup> (10 <sup>13</sup> )	
Coil Specification			0.0	10
Must Operate Voltage V		4	9.6	19
Must Release Voltage V		1	2 1	4
	ns diode fitted ns diode fitted	1 0.5	0.5	1 0.5
Resistance C		150	700	2000
Relay Specification	.2	130	700	2000
Isolation contact/coil k	·V		7	
Insulation resistance co			,	
	Omin (typical)		TBC	
Envirnonmental 2.	ziiiii (typicai)		100	
Operating Temp range °(	C:	-40 to +85		
Storage Temp range °(		-40 to +125		
0 1 0	Coil Volts Vdc — Isolation acros	s contacts kV		
\$8-0504 5	j	4		
S8-1204 1	2	4		
S8-2405 2	2.4	5		

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

## **Mechanical Dimensions**



Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

ISO9001 CERTIFIED

www.cynergy3.com

Pins 0.635mm Square ±0.05mm.
Pins 1 & 2 Tin over Nickel plated, on CuSn6 Phospher Bronze.
Pins 3 & 4 Tin plated on NiFe Nickel Iron.
Case Material Nylon.
Encapsulant: RTV627