

MODEL HDC-1

(PART NO. 980535)

Hold Down Clamp

- Prevents Vibration of Socket-mounted Relays
- For Use with Model 51X120 (8-Pin Socket)



DESCRIPTION

The **Hold Down Clamp** is constructed of stainless steel brackets and is joined with a rubber O-ring. The clamp is designed to secure the socket-mounted relay against vibration.

The Hold Down Clamp is attached to the Time Mark Model 51X120 8-Pin Socket with enclosed mounting hardware.

INSTALLATION

1. Attach the 2 metal brackets onto the opposite sides of the socket, as shown in the photo, with the 'hooked' side pointing downward.
2. Insert the relay into the socket.
3. Hook the rubber O-ring to one of the brackets, stretch it over the relay to the opposite side and hook it to the remaining bracket.

KIT INCLUDES:

- 2 Screws, #6-32 x 3/4"
- 2 Nuts, #6-32 x 5/16" (across flats)
- 2 L-Shaped Brackets, 0.65"x0.5"x0.3" (0.03" thick)
- 1 Neoprene O-Ring, 5"

Telephone: Main - (918) 438-1220
Sales - (800) 862-2875
Fax: (918) 437-7584

E-mail: sales@time-mark.com
Internet: <http://www.time-mark.com>



11440 East Pine Street
Tulsa, Oklahoma 74116

06/2018
© 2018 TIME MARK CORPORATION

TIME MARK is a division of  AEMT, Inc.

THIS PAGE LEFT BLANK

Telephone: Main - (918) 438-1220
Sales - (800) 862-2875
Fax: (918) 437-7584

E-mail: sales@time-mark.com
Internet: <http://www.time-mark.com>



11440 East Pine Street
Tulsa, Oklahoma 74116

06/2018
© 2018 TIME MARK CORPORATION

TIME MARK is a division of  AEMT, Inc.